



Alu Rundrohre aus EN AW-6060 T66 (ALMgSi 0,5 F22)

nach EN 573-3, 755-1/-2, DIN 1748-4, Herstellungslänge 6000 mm

O.D.	W.T.		O.D.	W.T.		O.D.	W.T.		O.D.	W.T.		O.D.	W.T.		O.D.	W.T.				
mm	mm		mm	mm		mm	mm		mm	mm		mm	mm		mm	mm				
6	1,0	○	20	3,0	○	30	5,0	○	48	3,0	○	60	4,0	○	80	4,0	○	120	5,0	○
8	1,0	○	20	5,0	○	32	1,5	○	48	4,0	○	60	5,0	○	80	5,0	○	130	5,0	○
10	1,0	○	22	2,0	○	32	2,0	○	50	1,5	○	60	10,0	○	80	10,0	○	140	5,0	○
10	2,0	○	25	2,0	●	35	2,0	●	50	2,0	●	65	5,0	○	90	3,0	○	150	3,0	○
12	1,0	○	25	2,5	○	35	3,0	○	50	2,5	○	70	2,0	○	90	5,0	○	150	5,0	○
12	2,0	○	25	3,0	○	40	1,5	○	50	3,0	●	70	3,0	●	100	2,0	○	160	3,0	○
15	1,0	○	25	4,0	○	40	2,0	●	50	4,0	○	70	5,0	○	100	2,5	○	160	5,0	○
15	1,5	○	25	5,0	○	40	3,0	●	50	5,0	○	70	7,0	○	100	3,0	○	180	5,0	○
16	2,0	○	28	1,5	○	40	4,0	○	50	10,0	○	75	5,0	○	100	4,0	○	200	5,0	○
18	2,0	○	30	1,5	○	40	5,0	○	50	5,0	○	76	3,0	●	100	5,0	○			
20	1,0	●	30	2,0	●	42	3,0	●	60	2,0	●	80	2,0	○	106	3,0	○			
20	2,0	●	30	3,0	○	45	3,0	○	60	2,5	○	80	2,5	○	108	4,0	○			
20	3,0	○	30	4,0	○	48	2,5	○	60	3,0	●	80	3,0	○	110	5,0	○			

- Lagervorrat
- Werksvorrat



Alu Quadratrohre aus EN AW-6060 T66 (ALMgSi 0,5 F22)

nach EN 573-3, 755-1/-2, DIN 1748-4, Herstellungslänge 6000 mm

Abmessung		Abmessung		Abmessung		Abmessung	
10 x 10 x 1,0	○	25 x 25 x 3,0	○	40 x 40 x 2,5	○	50 x 50 x 4,0	●
15 x 15 x 1,5	○	30 x 30 x 2,0	●	40 x 40 x 3,0	●	50 x 50 x 5,0	○
15 x 15 x 2,0	●	30 x 30 x 3,0	●	40 x 40 x 4,0	●	55 x 55 x 2,0	○
20 x 20 x 1,5	○	34 x 34 x 2,0	○	40 x 40 x 5,0	●	60 x 60 x 2,0	●
20 x 20 x 2,0	●	34 x 34 x 3,0	○	45 x 45 x 2,0	○	60 x 60 x 3,0	●
20 x 20 x 3,0	○	35 x 35 x 2,0	●	50 x 50 x 2,0	●	60 x 60 x 4,0	●
25 x 25 x 1,5	○	40 x 40 x 1,5	○	50 x 50 x 2,5	○	70 x 70 x 2,0	○
25 x 25 x 2,0	●	40 x 40 x 2,0	●	50 x 50 x 3,0	●	70 x 70 x 4,0	●
						80 x 80 x 2,0	○
						80 x 80 x 3,0	●
						80 x 80 x 4,0	●
						80 x 80 x 5,0	○
						90 x 90 x 4,0	○
						100 x 100 x 2,0	○
						100 x 100 x 2,5	○
						100 x 100 x 3,0	○
						100 x 100 x 4,0	○
						110 x 110 x 4,0	○
						120 x 120 x 2,5	○
						120 x 120 x 5,0	○
						150 x 150 x 5,0	○

Alu Rechteckrohre aus EN AW-6060 T66 (ALMgSi 0,5 F22)

nach EN 573-3, 755-1/-2, DIN 1748-4, Herstellungslänge 6000 mm

Abmessung		Abmessung		Abmessung		Abmessung	
20 x 10 x 1,5	○	40 x 25 x 3,0	○	60 x 25 x 2,0	○	80 x 40 x 2,5	○
20 x 10 x 2,0	●	40 x 30 x 2,0	●	60 x 30 x 2,0	●	80 x 40 x 3,0	●
20 x 15 x 2,0	●	40 x 30 x 2,5	○	60 x 30 x 3,0	○	80 x 40 x 4,0	●
25 x 15 x 2,0	○	40 x 30 x 3,0	●	60 x 34 x 3,0	○	80 x 50 x 2,0	○
25 x 20 x 2,0	●	40 x 30 x 4,0	○	60 x 40 x 2,0	●	80 x 50 x 3,0	○
30 x 10 x 1,5	○	45 x 25 x 2,0	○	60 x 40 x 2,5	○	80 x 50 x 4,0	○
30 x 15 x 2,0	○	50 x 15 x 2,0	○	60 x 40 x 3,0	○	80 x 60 x 3,0	○
30 x 20 x 2,0	●	50 x 20 x 2,0	●	60 x 40 x 4,0	●	80 x 60 x 4,0	○
30 x 20 x 3,0	○	50 x 20 x 3,0	●	60 x 50 x 3,0	○	100 x 18 x 2,0	○
30 x 25 x 2,0	○	50 x 20 x 4,0	○	60 x 50 x 4,0	○	100 x 20 x 2,0	●
34 x 20 x 2,0	○	50 x 25 x 3,0	○	70 x 30 x 2,0	○	100 x 25 x 2,0	○
34 x 20 x 3,0	○	50 x 30 x 2,0	●	70 x 30 x 3,0	○	100 x 30 x 2,0	○
35 x 20 x 2,0	○	50 x 30 x 2,5	○	70 x 40 x 3,0	○	100 x 30 x 3,0	●
35 x 25 x 2,0	○	50 x 30 x 3,0	●	80 x 20 x 2,0	●	100 x 40 x 2,0	○
40 x 15 x 2,0	○	50 x 40 x 2,0	○	80 x 20 x 2,5	○	100 x 40 x 2,5	○
40 x 20 x 1,5	○	50 x 40 x 2,5	○	80 x 30 x 2,0	○	100 x 40 x 3,0	●
40 x 20 x 2,0	●	50 x 40 x 3,0	○	80 x 30 x 3,0	○	100 x 40 x 4,0	●
40 x 20 x 3,0	○	50 x 40 x 4,0	○	80 x 30 x 4,0	○	100 x 50 x 3,0	●
40 x 25 x 2,0	○	60 x 20 x 2,0	●	80 x 40 x 2,0	●	100 x 50 x 4,0	●
						120 x 60 x 3,0	○
						120 x 60 x 4,0	○
						120 x 80 x 3,0	○
						140 x 40 x 4,0	○
						140 x 60 x 4,0	○
						140 x 80 x 4,0	○
						150 x 40 x 4,0	○
						150 x 50 x 4,0	○
						150 x 60 x 4,0	○

- Lagervorrat
- Werksvorrat