

# Blankstahl - Flach

nach DIN EN 10278

S235JRC+C DIN EN 10277

Abmessung	2	3	4	5	6	8	10	12	15	16	20	25	30	35	40	50	60
10		•															
12		•			•	•											
14	•																
15				•		•	•	•									
16		•				•											
18			•		•		•										
20		•	•	•	•	•	•	•	•								
22					•												
25				•	•	•	•	•	•	•	•						
30		•	•	•	•	•	•	•	•	•	•	•					
35				•	•	•	•	•	•		•	•					
40			•	•	•	•	•	•	•	•	•	•	•				
45			•			•	•	•	•	•	•	•					
50				•	•	•	•	•	•	•	•	•	•	•	•		
60				•	•	•	•	•	•	•	•	•	•	•	•	•	•
70					•	•	•	•	•		•	•	•		•	•	
80				•		•	•	•	•		•	•	•		•	•	•
90						•	•	•	•		•	•	•				
100				•	•	•	•	•	•	•	•	•	•		•	•	•
110							•		•		•						
120						•	•	•	•		•	•	•				
130					•	•	•		•		•						
140						•	•	•	•		•						
150				•		•	•	•	•		•	•	•				
160							•	•	•		•						
180							•	•	•		•						
200							•	•	•		•	•	•				
250							•	•	•		•	•					